

**TECHNICAL DATA** 

# Fluke 59 Mini Infrared Thermometer



## **Key features**

- Small in size easily fit in your pocket
- Laser targeting for fast, precise measurements
- Backlit display for easy reading in dark work areas
- 8:1 distance to spot ratios measures a 10 cm spot from 10 meters to target just what you want
- ± 2% basic accuracy gives you readings you can trust

#### **Product overview: Fluke 59 Mini Infrared Thermometer**

The Fluke 59 Mini Infrared Thermometer is the perfect combination of small size and big capability. With laserprecision targeting and 2% basic accuracy, the Fluke 59 Mini IR Thermometer enables professionals to diagnose heating and ventilation problems and monitor the temperature of electrical motors and electrical panels without contact. The 59 Mini puts quick, reliable temperature checks at your fingertips.

## Specifications: Fluke 59 Mini Infrared Thermometer

| Specifications    |                                 |                        |
|-------------------|---------------------------------|------------------------|
| Measurement range | - 18°C to 275°C (0°F to 525°F)  |                        |
| Accuracy          | 100°C - 275°C (212°F to 515°F): | ±2% of reading         |
|                   | 0°C - 100°C (32°F to 212°F):    | ±2°C(3.5°F) of reading |
|                   | Below 0°F (32°F):               | ±3°C(5.5°F) of reading |



| Repeatability           | ±1% of reading or ±1°C whichever is greater    |  |
|-------------------------|--|--|
| Emissivity              | Pre-set 0.95                                   |  |
| Distance-to-spot size   | 8:1 calculated @ 90% energy                    |  |
| Response time           | < 500ms  |  |
| Display resolution      | 0.2°C (0.5°F)                                  |  |
| Spectral range          | 6.5 – 18 um thermopile detector                |  |
| Display hold 7 seconds  | Yes  |  |
| LCD backlight           | Yes  |  |
| Temperature display     | °C or °F selectable                            |  |
| Low battery indicator   | Yes  |  |
| Ambient operating range | 0°C - 50°C (32°F to 120°F)                     |  |
| Relative humidity       | 10% - 90% RH non-condensing @ up to 30°C(86°F) |  |
| Storage temperature     | -20°C - 65°C(-4°F to 150°F) without battery    |  |
| Power                   | 9V battery included                            |  |
| Battery life            | 4 hours  |  |
| Weight                  | 200g, with battery                             |  |
| Dimensions (H x L x W)  | 152mm x 102mm x 38mm                           |  |
| Standards               | Conforms to EN 61326-1 electromagnetic         |  |
|                         | Emissions and susceptibility                   |  |
|                         | EN 61010-1 General safety                      |  |
|                         | EN 60825-1 Laser safety                        |  |
| Certification           | CE, CMC  |  |
| Warranty                | 1 year   |  |
|                         |  |  |



# **Ordering information**



#### FLUKE-59

Fluke 59 Mini Infrared Thermometer

Fluke 59 includes:

- Battery
- Quick Start Guide



### $\textbf{Fluke}. \ \textit{Keeping your world up and running}. \\ \textbf{\textcircled{\$}}$

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call: In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2023 Fluke Corporation. Specifications subject to change without notice. 02/2023

Modification of this document is not permitted without written permission from Fluke Corporation.